

JL7006D Datasheet

Zhuhai Jieli Technology Co.,LTD

Version: 1.5

Date: 2025.01.15

Copyright © Zhuhai Jieli Technology Co.,LTD. All rights reserved.

JL7006D Features

CPU

- 32bit Dual-Issue DSP
- Up to 160MHz programmable processor
- With IEEE754 Single precision FPU
- With cordic accelerate engine
- Advanced debug with 8 hardware breakpoints/watchpoints
- Advanced system exception capture unit

Interrupt

- Support for up to 64 interrupts with 8 priority level
- NMI supported
- SWI supported, with configurable priority
- Low power wake up by polling pending 12 IO interrupts for low power wake up

DSP Audio Processing

- SBC, AAC, LDAC, LHDC Audio decodes supported for BT audio
- mSBC voice codec supported for BT phone
- Supports MP2, MP3, WMA, APE, FLAC, AAC, MP4, M4A, WAV, AIF, AIFC audio decoding
- Packet Loss Concealment (PLC) for voice processing
- Single/Dual MIC Environmental Noise Cancellation (ENC)
- Multi-band DRC limiter
- 20-band EQ configuration for voice Effects
- Support Hi-Res Audio

Audio Codec

- Two channels 24-bit DAC, SNR \geq 103dB
- Two channels 24-bit ADC, SNR \geq 92dB
- DAC Sampling rates of 8kHz/11.025kHz/16kHz/22.05kHz/24kHz/32kHz/44.1kHz/48kHz/64kHz/88.2kHz/96kHz are supported
- ADC Sampling rates of 8kHz/11.025kHz/16kHz/22.05kHz/24kHz/

32kHz/44.1kHz/48kHz are supported

- Two analog MIC amplifier, build-in MIC bias generator
- Supports Four PDM digital MIC inputs
- Two channels analog AUX
- Supports cap-less, single-ended, and differential mode at the DAC path
- Supports 16ohm and 32ohm Speaker loading

ANC

- ANC processing engine up to 750 kHz sample rate
- 7.5 μ s analog to analog latency
- Supports 4 digital microphone inputs, 2 differential or single-ended analog inputs for ANC
- Supports Feed-Forward, Feed-Back, Hybrid ANC
- ANC module include 20 double precision Biquad filters for each FF/FB/ music compensation control

Bluetooth

- Compliant with Bluetooth V6.0+BR+EDR+BLE specification (DN Q334307)
- Meet class2 and class3 transmitting power requirement
- Support GFSK and DQPSK all packet types
- Provides maximum +10dbm transmitting power
- EDR receiver with minimum -94dBm sensitivity
- Fast AGC for enhanced dynamic range
- Support a2dp\avctp\avdtp\avrcp\hfp\spp\smp\att\gap\gatt\rfcomm\sdpl2cap profile a2dp 1.4\avctp 1.4\avdtp 1.3\avrcp 1.6.3\hfp 1.9\spp 1.2\rfcomm 1.2\pnp 1.3\hid 1.1.1\sdpcore 6.0\l2cap core 6.0

Peripherals

- One full speed USB 2.0 OTG controller
- Six multi-function 32-bit timers, support capture and PWM mode
- Three full-duplex basic UART, UART0, UART1 support DMA mode
- One hardware IIC interface supports host and device mode
- Three Built-in low power Cap Sense Keys
- LED controller, support 2 LED control by one IO
- 10-bit ADC for analog sampling
- External wake up/interrupt on all GPIOs
- Crossbar IO support: timer\SPI\SDC\IIC \UARTRDEC\ALINK\PLINK

PMU

- Low voltage LDO and DC-DC for internal digital and analog circuit supply

- Soft-off mode current:
Build-in LP_Touch off: $\leq 2\mu\text{A}$
Build-in LP_Touch on: $\leq 13\mu\text{A}$
- Built-in LDO and DC-DC for the core, I/O, Bluetooth and flash
- VBAT is 2.2V to 4.4V
- VDDIO is 2.2V to 3.6V

Packages

- QFN32(4mm*4mm)

Temperature

- Operating temperature: -40°C to $+85^{\circ}\text{C}$
- Storage temperature: -65°C to $+150^{\circ}\text{C}$

Applications

- Bluetooth TWS Earphones
- Bluetooth ANC TWS Earphones

Confidential

The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

1 Pin Definition

1.1 Pin Assignment




Figure 1-1 JL7006D Package Diagram

1.2 Pin Description

Table 1-1 JL7006D Pin Description

PIN NO.	Name	I/O Type	Drive (mA) 4 level	Function	Other Function
1	DAVSS	P	/		Analog Ground
2	NC				
3	IOVDD	PO	/		IO Power 3.3v
4	PB8	I/O	2.4~64	GPIO	AIN_B0; MIC1: MIC1 Input Channel; MIC1_P: Different MIC1 Positive; AMUX_B0: Analog Channel B0 L/R Input; UART0RXB: Uart0 Data Input(B); CAP4: Timer4 Capture.
5	PB5	I/O	2.4~64	GPIO	LP_TH4: Low Power Touch Channel 4; UART1TXA: Uart1 Data Output(A).
	PB7	I/O	2.4~64	GPIO	MIC_BIAS1: MIC1 Bias Output; MIC1_N: Different MIC1 Negative; AMUX_B1: Analog Channel B1 L/R Input; UART0TXB: Uart0 Data Output(B).
6	PB6	I/O	2.4~64	GPIO	ADC9: ADC Input Channel 9; UART1RXA: Uart1 Data Input(A); PWM2: Timer2 PWM Output.
7	PGND	P	/		DCDC Ground
8	SW	P	/		DCDC switch output, connected to inductor
9	VBAT	PI	/		Power Supply, connect to battery
10	VPWR	PI	/		Charge Power Input;
		I/O	8	GPIO	High Voltage Resistance I/O; UART0TXC: Uart0 Data Output(C); UART0RXC: Uart0 Data Input(C); PWM3: Timer3 PWM Output; CAP1: Timer1 Capture.
11	BTVDD	PO	/	GPIO	BT Power
12	PB3	I/O	2.4~64	GPIO	
	EVDD	PO	/		EVDD: Supply voltage to Peripherals
13	PB2	I/O	2.4~64	GPIO	LP_TH2: Low Power Touch Channel 2; ADC7: ADC Input Channel 7; CAP5: Timer5 Capture; UART2RXC: Uart2 Data Input(C);

Confidential

The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

					SPI2DOC: SPI2 Data Out(C).
14	PB1	I/O	2.4~64	GPIO (pull up)	Long Press Reset; LP_TH1: Low Power Touch Channel 1; UART2TXC: Uart2 Data Output(C); ADC6: ADC Input Channel 6; SPI2CLKC: SPI2 Clk(C).
15	P00	I/O	8		Test pin
	PB0	I/O	2.4~64		LP_TH0: Low Power Touch Channel 0; SPI2DIC: SPI2 Data Input(C); ALNK_MCLK(B): ALNK Master Clock(B); TMR4: Timer4 Clock Input.
16	BTRF	/	/		BT Antenna
17	NC				
18	XOSCI	I	/		XOSC In
19	XOSCO	O	/		XOSC Out
20	PC5	I/O	2.4~64	GPIO	SD0CLKA: SD0 Clock(A); UART2RXD: Uart2 Data Input(D); SPI1DOB: SPI1 Data Out(B); ALNK_DAT3(B): Audio Link Data3(B); IIC_SDA_B: IIC SDA(B); ADC5: ADC Input Channel 5.
21	PC4	I/O	2.4~64	GPIO	SD0CMDA: SD0 CMD(A); UART2TXD: Uart2 Data Output(D); SPI1CLKB: SPI1 Clock(B); ALNK_DAT2(B): Audio Link Data2(B); IIC_SCL_B: IIC SCL(B); ADC4: ADC Input Channel 4; PWM4: Timer4 PWM Output.
22	PC3	I/O	2.4~64	GPIO	SD0DATA: SD0 Data(A); UART0RXD: Uart0 Data Input(D); SPI1DIB: SPI1 Data In(B); ALNK_LRCK(B): Audio Link Word Select(B); IIC_SDA_C: IIC SDA(C); TMR3: Timer3 Clock Input.
23	PC2	I/O	2.4~64	GPIO	ALNK_SCLK(B): Audio Link Serial Clock(B); IIC_SCL_C: IIC SCL(C); UART0TXD: Uart0 Data Output(D); TMR1: Timer1 Clock Input.
24	USBDM	I/O	4	USB Negative Data	UART1RXD: Uart1 Data Input(D); IIC_SDA_A: IIC SDA(A); ADC11: ADC Input Channel 11;

Confidential

The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

					SPI2DOB: SPI2 Data Out(B); ISP_DI.
25	USBDP	I/O	4	USB Positive Data	UART1TXD: Uart1 Data Output(D); IIC_SCL_A: IIC SCL(A); ADC10: ADC Input Channel 10; SPI2CLKB: SPI2 Clock(B); ISP_CLK.
26	PA0	I/O	2.4~64	GPIO	MIC_LDO: MIC Power Supply
	PA2	I/O	2.4~64	GPIO	ALNK_MCLK(A): ALNK Master Clock(A); MIC_BIAS0: MIC0 Bias Output; MIC0_N: Different MIC0 Negative; AMUX_A1: Analog Channel A1 L/R Input; CAP3: Timer3 Capture; UART1RXC: Uart1 Data In(C); CLKOUT1.
27	PA1	I/O	2.4~64	GPIO	AIN_A0; MIC0: MIC0 Input Channel; MIC0_P: Different MIC0 Positive; AMUX_A0: Analog Channel A0 L/R Input; PWM0: Timer0 PWM Output; UART1TXC: Uart1 Data Output(C).
28	DACRP	O	/		Different DAC Right Positive Channel
29	DACRN	O	/		Different DAC Right Negative Channel
30	NC				
31	NC				
32	VCM	P	/		DAC reference voltage
/	Bom	P	/		Ground

P: Power or Ground PO:Power Output PI:Power Input I/O:Input or Output I:Input O:Output

Confidential

The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

2 Electrical Characteristics

2.1 Absolute Maximum Ratings

Table 2-1

Symbol	Parameter	Min	Max	Unit
Topt	Operating temperature	-40	+85	°C
Tstg	Storage temperature	-65	+150	°C
VBAT	Supply Voltage	-0.3	4.5	V
VPWR	Charger Voltage	-0.3	6	V
V _{3.0IO}	3.0V IO Input Voltage (IOVDD)	-0.3	3.6	V

Note : The chip can be damaged by any stress in excess of the absolute maximum ratings listed below.

2.2 PMU Characteristics

Table 2-2

Symbol	Parameter	Min	Typ	Max	Unit	Test Conditions
VBAT	Voltage Input	2.2	3.7	4.4	V	
VPWR	Charger supply Voltage	4.5	5.0	5.5	V	
Normal mode						
IOVDD	Voltage output	–	3.0	–	V	VBAT = 4.2V, 10mA loading
	Loading current	–	–	100	mA	IOVDD=3.0V@VBAT = 4.2V
BTVDD	Voltage output	–	1.25	–	V	IOVDD=3.0V, 10mA loading
	Loading current	–	–	60	mA	BTVDD=1.25V@IOVDD=3.0v
EVDD	Voltage output	–	1.1	–	V	BTVDD=1.25V, 1mA loading
	Loading current	–	–	5	mA	EVDD=1.1V@BTVDD=1.25v
LP mode						
IOVDD	Loading current			5	mA	IOVDD=3V@VBAT = 4.2V

2.3 Battery Charge

Table 2-3

Symbol	Parameter	Min	Typ	Max	Unit	Test Conditions
VPWR	Charge Input Voltage	4.5	5	5.5	V	–
V _{Charge}	Charge Voltage	4.15	4.2	4.25	V	VPWR > 4.5V

Confidential

The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

		4.30	4.35	4.40	V	VPWR > 4.65V
I _{Charge}	Charge Current	20		200	mA	Charge current at fast charge mode
I _{Trickl}	Trickle Charge Current	20	45	70	mA	V _{BAT} < V _{Trickl}

2.4 IO Input/Output Electrical Logical Characteristics

Table 2-4

IO input characteristics						
Symbol	Parameter	Min	Typ	Max	Unit	Test Conditions
V _{IL}	Low-Level Input Voltage	-0.3	—	0.3* IOVDD	V	IOVDD = 3.0V
V _{IH}	High-Level Input Voltage	0.7* IOVDD	—	IOVDD+0.3	V	IOVDD = 3.0V
IO output characteristics						
V _{OL}	Low-Level Output Voltage	—	—	0.33	V	IOVDD = 3.0V
V _{OH}	High-Level Output Voltage	2.7	—	—	V	IOVDD = 3.0V

2.5 Internal Resistor Characteristics

Table 2-5

Port	Drive(mA)				Internal Pull-Up Resistor	Internal Pull-Down Resistor	Comment
	2.4	8	26.4	64			
PA0~PA3 PB0~PB8 PC2~PC5					10K	10K	1、PB1 default pull up 2、USBDM & USBDP default pull Down 3、PC0, PP0(VPWR), P00 are high voltage resistance to 5V 4、internal pull-up/pull-down resistance accuracy ±20%
PP0(VPWR), P00	8				10K	10K	
USBDP	4				1.5K	15K	
USBDM	4				180K	15K	

2.6 DAC Characteristics

Table 2-6

Parameter	Min	Typ	Max	Unit	Audio Format	Test Conditions
Frequency Response	20	—	20K	Hz	—	Differential Mode

Confidential

The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

Output Swing		0.55	0.74	Vrms	–	1KHz/0dB
THD+N	–	-76	–	dB	PCM	32 ohm loading
	–	-68.7	–	dB	SBC	With A-Weighted Filter
S/N	–	100.4	102	dB	PCM	Filter
	–	98.7	–	dB	SBC	
Dynamic Range	–	100	–	dB	PCM	Differential Mode
	–	99.1	–	dB	SBC	1KHz/-60dB 32 ohm loading With A-Weighted Filter
Noise Floor		6.0		uV	–	A-Weighted Filter
DAC Output Power	–	20	30.0	mW	–	Differential Mode 16ohm loading

2.7 ADC Characteristics

Table 2-7

Parameter	Min	Typ	Max	Unit	Test Conditions
Dynamic Range		95		dB	Fsample=44.1kHz Fin=1KHz 2mVpp Input
S/N	–	95	–	dB	Fsample=44.1kHz Fin=1KHz 2Vpp Input
THD+N	–	-72	–	dB	
Crosstalk	–	-80	–	dB	

2.8 BT Characteristics

2.8.1 Transmitter

Basic Rate

Table 2-8

Parameter	Min	Typ	Max	Unit	Test Conditions
RF Transmit Power		7	9	dBm	25°C, Power Supply VBAT=3.7V 2441MHz
RF Power Control Range		18		dB	
20dB Bandwidth		950		KHz	
In-band spurious	F=F ₀ ±1MHz	-19		dBm	
Emissions (BQB Test Mode RF_Tx Power=5dBm)	F=F ₀ ±2MHz	-48		dBm	
	F=F ₀ ±3MHz	-50		dBm	
	F=F ₀ +/->3MHz	-55		dBm	

Confidential

The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

Enhanced Data Rate**Table 2-9**

Parameter		Min	Typ	Max	Unit	Test Conditions
Relative Power			-2		dB	25°C, Power Supply
$\pi/4$ DQPSK Modulation Accuracy	DEVM RMS		5		%	
	DEVM 99%		13		%	
	DEVM Peak		10		%	
In-band spurious Emissions (BQB Test Mode RF_Tx Power=5dBm)	$F=F_0 \pm 1\text{MHz}$		-1.5		dBm	VBAT=3.7V 2441MHz
	$F=F_0 \pm 2\text{MHz}$		-28		dBm	
	$F=F_0 \pm 3\text{MHz}$		-42		dBm	
	$F=F_0 + / - > 3\text{MHz}$		-45		dBm	

2.8.2 Receiver**Basic Rate****Table 2-10**

Parameter		Min	Typ	Max	Unit	Test Conditions
Sensitivity			-92		dBm	25°C, Power Supply
Co-channel Interference Rejection			-10		dB	
Adjacent Channel Interference Rejection	+1MHz		+4		dB	
	-1MHz		+2		dB	
	+2MHz		+38		dB	
	-2MHz		+38		dB	
	+3MHz		>+40		dB	
	-3MHz		+34		dB	

Enhanced Data Rate**Table 2-11**

Parameter		Min	Typ	Max	Unit	Test Conditions
Sensitivity			-93		dBm	25°C, Power Supply
Co-channel Interference Rejection			-11		dB	
Adjacent Channel Interference Rejection	+1MHz		+4		dB	
	-1MHz		+2		dB	
	+2MHz		+38		dB	
	-2MHz		+38		dB	
	+3MHz		>+40		dB	
	-3MHz		+34		dB	

Confidential

The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

2.9 ESD Protection

Table 2-12

Parameter	Typ.	Test pin	Reference standard
Human Body Mode	$\pm 4\text{KV}$	All pins	JEDEC EIA/JESD22-A114
Machine Mode	$\pm 200\text{V}$	All pins	JEDEC EIA/JESD22-A115
Charge Device Model	$\pm 1\text{KV}$	All pins	JEDEC EIA/JESD22-C101F
Latch up	$\pm 200\text{mA}$	All GPIO pins	JEDEC STANDARD NO.78E
	$1.5 \times V_{\text{opmax}}$	All power pins	

Note : $1.5 \times V_{\text{opmax}}$ = 1.5 times maximum operating voltage.



3 Package Information

3.1 QFN32_4.0x4.0





Figure 3-1 JL7006D Package

4 IC Marking Information



- ① LLLLLL: Production Batch
- ② JL700Nx: Chip Model
- ③ x: Built-in flash size
 - 0: No Flash Memory
 - 2: 2Mbit Flash
 - 4: 4Mbit Flash
 - 8: 8Mbit Flash
 - 6: 16Mbit Flash
 - 3: 32Mbit Flash

5 Solder-Reflow Condition




Figure 5-1 Classification Reflow Profile

Classification Profiles

Table 5-1

Profile Feature		Sn-Pb Eutectic Assembly	Pb-Free Assembly
Preheat /Soak	Temperature Min (T_{smin})	100°C	150°C
	Temperature Max (T_{smax})	150°C	200°C
	Time (t_s) from (T_{smin} to T_{smax})	60-120 seconds	60-180 seconds
Average ramp-up rate (T_{smax} to T_p)		3°C/second max	3°C/second max
Liquidous temperature (T_L)		183°C	217°C
Time (t_L) maintained above T_L		60-150 seconds	60-150 seconds
Peak package body temperature (T_p)		See Table 5-2	See Table 5-3
Time within 5°C of actual Peak Temperature (t_p) ²		10-30 seconds	20-40 seconds
Ramp-down rate (T_p to T_L)		6°C/second max	6°C/second max
Time 25°C to peak temperature		6 minutes max	8 minutes max

Note 1: All temperatures refer to topside of the package, measured on the package body surface.

Note 2: Time within 5°C of actual peak temperature (t_p) specified for the reflow profiles is a “supplier” minimum and “user” maximum.

SnPb - Classification Temperature

Table 5-2

Package Thickness	Volume mm ³ < 350	Volume mm ³ ≥ 350
<2.5 mm	240 +0/-5°C	225 +0/-5°C
≥2.5 mm	225 +0/-5°C	225 +0/-5°C

Pb-free - Classification Temperature **Table 5-3**


Package Thickness	Volume mm³ < 350	Volume mm³ 350 - 2000	Volume mm³ > 2000
< 1.6mm	260°C	260°C	260°C
1.6 mm - 2.5mm	260°C	250°C	245°C
> 2.5mm	250°C	245°C	245°C

**Confidential**

The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

6 Revision History

Date	Revision	Description
2022.05.14	V1.0	Initial Release
2022.07.13	V1.1	Update Soft-off mode current consumption
2022.07.19	V1.2	Update Package Information & Add ANC Mode description
2023.11.22	V1.3	Update JL7006D BT_Features
2024.08.26	V1.4	Update JL7006D Audio_Features Update DAC Characteristics
2025.01.15	V1.5	Update Bluetooth Vision and profiles



Confidential

The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.